

Quick Tests for Correct Adjustment

What about my growing puppy?

The NewTriX™ dog halter is fully adjustable to accommodate different breeds and growing dogs. A puppy may start in his adult-sized halter (or for large dogs, a size or two smaller), with shortened Chin Straps and Cheek Straps. These can be gradually lengthened as your puppy grows.


Dogs with wide and short snouts will need relatively shorter Cheek Straps and longer Chin Straps; dogs with narrow, long snouts will need relatively longer Cheek Straps and shorter Chin Straps.

"We chose the NewTriX™ dog halter after trying everything else. It is kinder to the dogs and easier for our volunteers to use in our foster program. The NewTriX™ dog halter is simply the best dog training tool on the market."

Christ Fowler, National Service Dogs




Cheek Straps will be a little loose and pucker slightly. Fleece-lined Nose Strap will not ride up into dog's eyes. To make corrections see: **Cheek Strap Adjustments** on reverse.



With a correctly adjusted Nape Strap you will not be able to pull the Nose Strap forward off the dog's snout. Long-nosed dogs may tolerate a looser adjustment. See **Instruction 6 on reverse**



Your dog will be able to open his mouth wide. To make a correction see: **Chin Strap Adjustments** on reverse.



Cheek and Chin Straps will be equal on both sides.

Teaching your dog NewTriX

- When introducing the NewTriX™ dog halter take the time to create positive associations. With a food treat, **lure** your dog to put his nose through the halter; position the straps while he's busy eating.
- **Distract** your dog from pawing at the NewTriX™ dog halter and **reward** him with food, praise and attention when he leaves it alone.
- **Practice** a loose leash walk in an enclosed area where your dog has no strong **motivation** to go elsewhere.
- **Resist** your dog's pull with a brief pulse of tension to **halt** his forward motion. If he continues to pull, the halter will apply gentle pressure symmetrically around his snout and head to restrain him. Releasing the tension is a powerful **reinforcement** for him to stop pulling.
- Move **forward** when the leash is **loose**.
- See www.newtrix.ca for video demonstration.

Visit our website for videos and more training tricks.

www.newtrix.ca



Patented: US 6,595,156 EP 108 2003, CAN 2,334,019

NewTriX Inc.

348-2255B Queen St. E.
Toronto, Ontario
Canada M4E 1G3

1.866.384.2135
F 416.698.5774

easyway@newtrix.ca
www.newtrix.ca



dog halter
www.newtrix.ca

instructions

newtrix.ca

The NewTriX™ dog halter stops pulling

with calm, kind control.



Pressure on the front of a dog's neck or chest triggers an automatic reaction called the **opposition reflex**. This is a motor neuron response which actually encourages pulling. It renders millions of dogs a tremendous challenge to manage on leash.

The solution is simple.

Reverse it!


When your dog pulls, the NewTriX™ dog halter applies pressure **behind** his head which **triggers** the opposition reflex, but this time your dog **leans back** into it and **stops pulling!** The patented **push-pulley** mechanism applies pressure on the **back of your dog's neck** and **instantly** puts this incredible force to work *for* you.

Stop pulling at its true source.

No pain, no fear. Pure science.


Fitting the NewTriX Dog Halter

newtrix.ca




1. The NewTriX dog halter is comprised of 8 main parts: the fleece-lined Nose Strap, the Cheek and Chin Straps, the Side and Back Adjustment Slides, the Lateral Pivot Rings, the Nape Strap, and the Safety Lanyard.

Grasp the halter by the fleece-lined Nose Strap, allowing the rest of the halter to dangle. Straighten the straps of the halter so they will sit flat against your dog's face and neck.



2. Identify the two Lateral Pivot Rings which link the Cheek and Chin Straps to the Nape Strap. These rings will sit on the sides of your dog's neck. The Nape Strap slips between these two rings to form the Push-Pulley mechanism.


With one finger pull down on the Nape Strap between the Lateral Pivot Rings thus forming the Push-Pulley which will sit behind your dog's head. You may need to move the Back Adjustment Slide each time to create an opening large enough for your dog's head.




3. With a food treat, lure your dog to put his nose through the opening you've created.



4. Place the fleece-lined Nose Strap on your dog's snout and while he's busy with the treat slip the Nape Strap over his ears.



5. Make sure the Chin Straps do not get into his mouth and that they crisscross under his chin. The ring under your dog's chin is merely to keep these straps from tangling.



6. Cinch up the Back Adjustment Slide on the Nape Strap so as to prevent the Nose Strap from slipping forward off the snout.



7. Connect the Safety Lanyard to your dog's regular flat collar. Connect your leash to the ring on the end of the Nape Strap. Please read **Teaching Your Dog NewTriX** on the reverse. Enjoy your walk!



Cheek Strap Adjustments:

Check the fit on your dog's face and remove the halter to make adjustments. Adjust the Cheek Straps equally on both sides, so they fit loosely and will pucker slightly. The Cheek Straps' function is to prevent your dog from pawing the nose strap forward off his snout. If the Cheek Straps are too short they will pull the Nose Strap toward your dog's eyes, so lengthen the Cheek Straps.



Chin Strap Adjustments:

Check the fit on your dog's face and remove the halter to make adjustments. Your dog should be able to yawn fully. Pull the Chin Straps through the Adjustment Slides, shortening or lengthening the distance between the Adjustment Slide and the Lateral Pivot Ring. If your dog is on the lower end of the weight range for its size, there will be a greater amount of strap 'in reserve' between these points. This reserve can be fed into the Chin and Cheek Strap segments as your dog grows.

SATISFACTION GUARANTEED

NewTriX Inc. warrants the NewTriX™ dog halter will be free from defects in materials, workmanship and design affecting normal use, for a period of one year from the original retail purchase date. All claims under this warranty must be submitted, in writing, to NewTriX Inc., with original proof of purchase. In the event that NewTriX Inc., in its sole discretion, finds a defect covered by this limited warranty, NewTriX Inc. will repair, replace or refund the defective product. NewTriX Inc. liability is limited to the value of the product. There are no other warranties, express or implied. NewTriX Inc. is not responsible for indirect, special, incidental or consequential damages of any kind resulting from any breach of warranty, negligence or negligent manufacture.